



EXPORT PRODUCT CATALOGUE

Auto Tyres & Tubes

Two-wheeler, three-wheeler and commercial vehicle tyres, and butyl tubes from scooter to truck. Manufactured in India for export.



STORM



GLIDE



SWIFT



PRIME



TUSKER



CROWN

1990

ESTABLISHED



EXPORT EDITION
– SEPTEMBER
2026

yokostonne.com

CONTENTS

The range

Six tyre patterns and the butyl tube range, with the sizes and fitments each is supplied in. Sizes and weights are collected in the index at the back.

STORM 03

Motor cycle · 3.00-18 TT · 3.00-17 TT · 2.75-18 TT

GLIDE 04

Motor cycle · 2.75-18 TT · 2.75-17 TT

SWIFT 05

Scooter · motor cycle · 90/90-12 TT · 90/100-10 TL · 80/100-18 TL

PRIME 06

Scooter · motor cycle · 90/90-12 TT · 90/100-10 TL · 80/100-18 TL

TUSKER 07

E-rick · 3.75-12 TT

CROWN 08

E-rick · 4.00-8 TT

BUTYL TUBES — TWO-WHEELER 09

Scooter · e-bike · motor cycle · bullet

BUTYL TUBES — COMMERCIAL 10

Three-wheeler · car radial · truck · tractor · flap

REFERENCE

SIZE INDEX — EVERY PATTERN, ITS SIZES AND ITS WEIGHT RANGE 11

MOTOR CYCLE RANGE

Storm

The motor cycle pattern, in three sections across 17 and 18 inch rims.

SIZES AVAILABLE

WEIGHT (G)

3.00-18 TT	3550 ± 50
3.00-17 TT	3450 ± 50
2.75-18 TT	3050 ± 50



MOTOR CYCLE RANGE

Glide

The 2.75 section in 17 and 18 inch, for the front wheel.

SIZES AVAILABLE

WEIGHT (G)

2.75-18 TT	2850 ± 50
2.75-17 TT	2750 ± 50



SCOOTER · MOTOR CYCLE

Swift

The front fitment for scooter and motor cycle, in tube-type and tubeless. Pairs with Prime as a matched set.

SIZES AVAILABLE

FITMENT

WEIGHT (G)

90/90-12 TT	Scooter	2550 ± 50
90/100-10 TL	Scooter	2750 ± 50
80/100-18 TL	Motor cycle	3400 ± 50



SCOOTER · MOTOR CYCLE

Prime

The driven-wheel fitment matching
Swift, in the same sizes and in tube-type
and tubeless.

SIZES AVAILABLE	FITMENT	WEIGHT (G)
90/90-12 TT	Scooter	2550 ± 50
90/100-10 TL	Scooter	2750 ± 50
80/100-18 TL	Motor cycle	3500 ± 50



E-RICK RANGE

SIZES AVAILABLE

WEIGHT (G)

Tusker

3.75-12 TT

3200 ± 50

The wide three-wheeler section for e-rickshaw duty, carrying passenger load on unsurfaced roads.



E-RICK RANGE

SIZES AVAILABLE

WEIGHT (G)

Crown

4.00-8 TT

3800 ± 50

The 8 inch three-wheeler fitment, matched by the 4.00-8 butyl tube on page 10.



BUTYL RUBBER

Two-wheeler tubes

Butyl tubes for scooter, e-bike, motor cycle and bullet fitments. Three-wheeler, car, truck and tractor sizes follow on page 10.

VARIANTS

COMPOUND	Butyl rubber
CONSTRUCTION	Moulded
VALVE	TR-29 · V10801 · V10803
SUPPLY	Bundled



RANGE	SIZE	WEIGHT (G)	VALVE
SCOOTER	3.50-8	340 ± 20	V10803
	3.50-10	410 ± 20	V10801
	2.75 / 3.00-10	320 ± 20	V10801
E-RICK	90/90-12	390 ± 20	V10801
E-BIKE	3.75 / 4.00-12	500 ± 20	V10801
	2.75 / 3.00-14	420 ± 20	TR-29
MOTOR CYCLE	2.25 / 2.50-16	340 ± 20	TR-29
	2.25 / 2.50-17	350 ± 20	TR-29
	2.75 / 3.00-17	430 ± 20	TR-29
	100/90-17	530 ± 20	TR-29
	2.75 / 3.00-18	460 ± 20	TR-29
	3.00-18	500 ± 20	TR-29
	100/90-18	540 ± 20	TR-29
BULLET	3.25 / 3.50-19	640 ± 20	TR-29

BUTYL RUBBER

Three-wheeler, car, truck & tractor tubes

RANGE	SIZE	WEIGHT (G)	VALVE
AUTO RICKSHAW	4.00-8	460 ± 20	V10803
	4.00-8	460 ± 20	TR-13
	4.00-10	550 ± 20	TR-13
	4.50-10	630 ± 20	TR-13
CAR RADIAL	145 / 155 70 R13	790 ± 50	TR-13
	175/65 R14 · 165 65/80 R14	1000 ± 20	TR-13
	195/80 R15 · 205/65 R15	1400 ± 50	TR-13
	195/55 R16 · 205/215 65 R16	1500 ± 50	TR-13
ULTRA TRUCK	145 / 155 / 165-12	780 ± 20	TR-13
TRUCK	7.50-16 / 8.25-16 LV	1950 ± 50	AB1582
	8.25-20	2650 ± 20	TR-175A
	9.00-20	3000 ± 100	TR-175A
	10.00 R20	4050 ± 50	TR-78A
TRACTOR	6.00-16	1100 ± 100	TR-15
ADV	5.00-19	1150 ± 20	TR-14
FLAP	9.00 / 10.00-20 20N	—	—

VALVE TYPES

 TR-29 Motor cycle, bullet and 14 inch e-bike	 V10801 10 and 12 inch scooter and e-bike	 V10803 3.50-8 scooter and 4.00-8 rickshaw
 TR-13 Rickshaw, car radial and 12 inch ultra truck	 TR-14 5.00-19 ADV	 TR-15 6.00-16 tractor
 TR-175A 8.25-20 and 9.00-20 truck	 TR-78A 10.00 R20 truck radial	 AB1582 7.50 / 8.25-16 LV truck

Valve profiles are shown as diagrams. Long-neck stems and other valve types are supplied to order and confirmed on the proforma.

INDEX

Sizes and weights

Every tyre pattern, the sizes it is supplied in and its fitment. TL denotes a tubeless fitment and TT a tube-type fitment. Motor cycle and scooter patterns are also supplied as matched front-and-rear sets, quoted on request. Weights are per piece across the listed sizes, ± 50 g. Tube sizes are listed on pages 08 and 09.

PATTERN	SIZES AVAILABLE	FITMENT	WEIGHT RANGE
STORM	3.00-18 TT · 3.00-17 TT · 2.75-18 TT	Motor cycle	3.05–3.55 kg
GLIDE	2.75-18 TT · 2.75-17 TT	Motor cycle, front	2.75–2.85 kg
SWIFT	90/90-12 TT · 90/100-10 TL · 80/100-18 TL	Scooter · motor cycle	2.55–3.40 kg
PRIME	90/90-12 TT · 90/100-10 TL · 80/100-18 TL	Scooter · motor cycle	2.55–3.50 kg
TUSKER	3.75-12 TT	E-rick · three-wheeler	3.20 kg
CROWN	4.00-8 TT	E-rick · three-wheeler	3.80 kg

Enquiries

Container-load quantities, mixed loads and private-label moulds on request. Send your size and pattern requirement and we will quote against it.

WRITE TO

sales@yokostonne.com
+91 80 4132 0094 / 95

OFFICES

A33/1, DLF Phase 1
Gurugram, Haryana 122002
India

1110 A Mittal Towers
MG Road, Bangalore 560001
India



ISI marked · BIS certified · ISO 9001:2015 · IATF 16949:2016